

X-17



► FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 3ms response time
- High 3000:1 dynamic contrast ratio
- DVI ready for high quality signal
- S-Video and CVBS inputs
- Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- Auto-adjustment for optimal settings
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white

► SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	3000:1 (DCR)
	Viewing Angle (H/V)	160°/160° (Typical)
	Display Color	16.7M
	Response Time	3ms (GTG)
	Frequency (H/V)	H: 30kHz - 80kHz V: 56Hz - 76Hz
Input	Max. Pixel Clock	160MHz
	Life Time	50,000hrs (Minimum)
	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
Connector	S-Video	4-Pin Mini Din S-Video
	CVBS	CVBS Jack
	Power	3-Pin AC Plug
	Thickness	3.0mm (0.18")
NeoV Optical Glass	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +15°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/S, CE, BSMI, CB, ISO 13406-2, Energy Star, GOST, WEEE, RoHS
	VESA	DDC-2B, DPMS, DDC-CI
Power	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off)
	Net (W x H x D)	408 x 398 x 175mm (16.1" x 15.7" x 6.9")
Dimensions	Packing (W x H x D)	495 x 510 x 228mm (19.5" x 20.0" x 9.0")
	Net Weight	6.8Kg (13.9lbs)
Weight	Gross Weight	9.5Kg (20.9lbs)
	1 Pallet	40 Cartons
Packing	20' Container	360 Sets
	40' Container	840 Sets

All specifications are subject to change without prior notice



www.agneovo.com

Copyright © 2008 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.